

YOU NEVER KNOW WHAT CHALLENGES YOU WILL FACE. THAT'S WHY YOU ARM YOURSELF WITH VERSATILE TOOLS THAT CAN HELP YOU GET THE JOB DONE. AND WHY SHURTAPE OFFERS A FULL LINE OF TAPES THAT ARE ENGINEERED FOR PERFORMANCE.

FROM EXCELLENT ADHESION AND HOLDING POWER TO EASY HAND TEARABILITY AND CLEAN REMOVAL, YOU CAN TRUST SHURTAPE TO DELIVER THE PRODUCT FEATURES YOU CAN RELY UPON TO GET THE JOB DONE QUICKLY AND EFFICIENTLY TO SAVE YOU TIME AND MONEY.

EV 57B



General purpose grade, 7.0 mil vinyl insulating tape for use in a variety of mechanical and electrical applications. UL Listed and CSA Approved, EV 57B is a highly conformable, lead free and flame retardant black electrical tape for use indoors and out.

EV 57C



General purpose grade, 7.0 mil vinyl insulating tape for use in a variety of mechanical and electrical applications, including color-coding and phasing tasks. EV 57C is UL Listed and CSA Approved, and is a highly conformable, lead free and flame retardant colored electrical tape for use indoors and out.

EV 77B



Professional grade, 7.0 mil, all-weather vinyl insulating tape used for electrical and mechanical protection in temperatures ranging from 0 F to 220 F. UL Listed and CSA Approved, EV 77B black electrical tape is lead free, flame retardant, and is engineered with a polymeric backing construction, as well as a specialized method of bonding the adhesive to the vinyl backing, which allows the tape to be highly conformable and deliver a moisture-tight seal, even in extreme temperatures.

EV 77C



Professional grade, 7.0 mil, all-weather vinyl insulating tape used for color-coding and phase identification in electrical applications. UL Listed and CSA Approved, EV 77C colored electrical tape is lead free, flame retardant and is engineered with a polymeric backing construction, as well as a specialized method of bonding the adhesive to the vinyl backing, which allows the tape to be highly conformable and deliver a moisture-tight seal, even in extreme temperatures.

EV 97B



Premium grade, 8.5 mil, all-weather vinyl tape used for insulating electrical splices up to 600 V, as a jacketing on high voltage splices and repairs, and can also be used when wrapping wire harnesses and cables. EV 97B is UL Listed, CSA Approved, lead free and flame retardant, and is engineered with polymeric backing construction, as well as a specialized method of bonding the adhesive to the vinyl backing, which creates a highly conformable tape that delivers a moisture-tight seal.

PW 100



General purpose, corrosion-resistant PVC tape for use on under and above ground pipe installations. PW 100 pipe wrap tape offers excellent moisture resistance and conformability to protect metal and plastic tubing.

GS 500



Utility grade, 150 lb., fiberglass reinforced strapping tape for general purpose strapping, packaging, bundling and palletizing jobs. Offering high adhesion and a backing that resists splitting and cracking, GS 500 tackles a variety of jobs with ease.

AP 101®



General purpose grade, 1.6 mil, acrylic packaging tape designed for closure of lightweight boxes. Durable BOPP film provides strength and flexibility, while a high-quality adhesive gives AP 101® clarity, UV resistance, premium aging characteristics and low odor to tackle the task at hand.

AP 201®



Production grade 2.0 mil, acrylic packaging tape for light- to medium-weight box sealing. AP 201® offers a 28 micron cast BOPP film backing and high-quality adhesive engineered to deliver clarity, UV resistance, premium aging characteristics and low odor.



FrogTape™ Pro Grade Flashing Tape's high-performance acrylic adhesive sticks, resticks and stays stuck to the roughest surfaces, in the toughest weather. So, you stay in control when it matters most.



FSL 55 FrogTape™



Pro grade flashing tape for creating weatherproof seals around windows and doors in residential and commercial applications.

FSL 55 FrogTape™



Pro grade flashing and waterproofing tape for building transitions, deck ledgers and waterproofing above grade construction applications.



SHURTAPE.COM
1.888.442.TAPE



Shurtape
TECHNOLOGIES



Shurtape
INDUSTRIAL

Industrial Construction & Restoration Tapes



When performance cannot be compromised, FrogTape® delivers professional results you can trust — when it matters most. The family includes CF 120/Multi-Surface (green), CF 160/Delicate Surface (yellow) and CP 130/Pro Grade (blue) formulations that feature PaintBlock® Technology, a super-absorbent polymer that seals tape edges to keep paint out and lines sharp, in addition to CP 199/Pro Grade Orange™ for production painting (does not contain PaintBlock Technology).

And now, the best just got better with CF 180/ FrogTape Advanced™ featuring PaintBlock Technology, plus advanced performance in conformability and shred-resistance.

CP 66®



Contractor grade, high adhesion masking tape for residential and commercial painting, holding and packaging, particularly those applications that demand quick stick and conformability to irregularly shaped surfaces. CP 66® is engineered with a rubber-based adhesive, unwinds easily and can be used in temperatures from 50 F to 150 F.

CP 27®



Professional grade, medium adhesion painter's tape for interior and exterior masking of multiple surfaces, such as painted walls, glass, vinyl, metal and wood, when easy, no-residue removal is a must. CP 27® is designed with a rubber-based adhesive that prevents lifting and paint seepage, while allowing it to remove cleanly from surfaces without damage for up to 14 days to deliver superior results.

CP 105



General purpose grade, medium-high adhesion masking tape for non-critical bundling and labeling applications. CP 105 provides excellent surface contact on a range of substrates.

FP 227



High adhesion masking tape, available in a variety of colors, including high-visibility fluorescents, used for labeling and color-coding tasks on a variety of surfaces, including vinyl, metal, glass, plastic and rubber. FP 227 is flexible, unwinds easily and is resistant to abrasion and oil.

MJ 100



Open weave fiberglass mesh tape used for reinforcing joints, seams and connections when paint-on mastic is used in HVAC applications, and can also be applied to drywall seams before the application of joint compound. MJ 100 drywall tape is self-adhering and offers superior strength compared to paper.

DS 154 FrogTape®



Professional grade, double-sided poly-hanging containment tape used for creating high-performance containment systems for restoration, abatement and remodeling tasks such as painting, cleaning, sanding, mold remediation, asbestos removal and more. With a premium painter's tape adhesive on one side and an aggressive adhesive on the other that securely holds protective coverings, DS 154 is an easy-to-use, one step solution.

PC 745 T-Rex®



Super-tough, premium co-extruded cloth tape for all-weather use on rough surfaces, for heavy duty repairs, and can also be used as a bottom board tape in the manufactured housing industry. A "monster" of a tape, T-Rex® PC 745 combines a waterproof, reinforced backing with twice the adhesive to deliver a ferociously strong tape with unrivaled staying power



RSW 500 T-Rex®



T-Rex Waterproof & Repair Tape is engineered with Flex-to-Fit Technology™ to provide maximum stretch around objects and offers extreme weather performance for indoor and outdoor fixes.



PC 9S/C



Duck Pro® by Shurtape® general purpose grade cloth duct tape featuring aggressive adhesive and cold temperature performance for sealing, seaming, repairing and holding applications as well as for tasks in the restoration industry, such as holding poly-sheeting. A repair duct tape, PC 9S (silver) and PC 9C (colors) provide superior adhesion with 30-day indoor clean removal.



AF 914CT/975CT



Lined cold temperature aluminum foil tape for joining and sealing aluminum-backed and fibrous insulation and metal ductwork, and to repair metal and sheet metal. Both AF 914CT and AF 975CT deliver an airtight seal in temperatures ranging from -20 F to 260 F. AF 914CT is 1.5 mil; AF 975CT is 2.0 mil.



AF 984CT



UL 723 tested Foil/Scrim/Kraft (FSK) tape for sealing seams in scrim-reinforced duct insulation. Ideal for applications that demand a maximum-strength tape, AF 984CT is lined, offers an acrylic adhesive and can be used in temperatures ranging from -20 F to 260 F.



AF 099



Aluminum foil HVAC tape for joining and sealing joints, connections and seams on rigid fiberglass ductboard and flexible air duct, and as a UL 181A-P listed product, can also be used in place of mechanical fasteners on rigid ductboard. UL 181A-P/B-FX Listed and printed, AF 099 delivers full system closure by forming airtight bonds on joints and seams in temperatures ranging from -20 F to 260 F and in humid conditions.



PC 622



Premium grade cloth duct tape used for protecting window and door frames during stucco application, as well as for various applications in high performance motorsports and for heavy duty bundling, holding and splicing. PC 622 combines high tensile strength, excellent holding power and conformability to deliver a tape solution that can withstand the rigors of the job.



PC 608



PC 608 Duck Pro® by Shurtape® general purpose grade, co-extruded abatement duct tape for use when building containments and a variety of other applications in remediation, restoration and abatement jobs, including mold and asbestos removal. PC 608 combines a high-tack, high-performing cold temperature adhesive with good conformability to a variety of surfaces to deliver exceptional performance when hanging poly-sheeting.



CP 327



Professional grade blue containment tape for use on interior and exterior walls, glass, vinyl, metal and wood, when building containment systems for restoration, remodeling, remediation and abatement jobs. Built for strength and durability, CP 327 features a rubber-based adhesive that prevents containment failure, while allowing it to remove cleanly from surfaces without damage for up to 21 days to deliver superior results.



FP 97



General purpose grade flatback paper tape used for floor protection seaming, box sealing, splicing, binding, holding, tabbing, reinforcing, banding and patching applications. FP 97 is constructed with an aggressive adhesive that offers excellent holding power and a strong, flexible kraft backing.

PE 333



Non-UV-resistant polyethylene film tape used to mask surfaces, such as windows and doors, during stucco application and painting, as well as for seaming underslab vapor barriers and holding poly-sheeting when building containments. Designed with a special, high-tack synthetic adhesive, PE 333 maintains a watertight seal, even in severe environments and weather conditions, and removes cleanly when the job is done.

PE 444



UV-resistant polyethylene film tape used to mask surfaces, such as windows and doors, during stucco application and painting. PE 444 is a stucco masking tape engineered for outdoor use, offering a special, high-tack synthetic adhesive that maintains a watertight seal, even in severe environments and weather conditions, and clean removal when the job is done.

FP 227



BT 100



Non-adhesive barricade tape for marking restricted areas and managing access to work sites by professionals in the safety, construction, utilities, hardware and other industries. BT 100 features 2-inch letters that are easy to read, is resistant to moisture and humidity and resists sagging for long-term use. Available text includes: Lead Hazard and Wet Paint (English only); Caution and Danger (available bilingual English/Spanish).


VP 410



UV-resistant SPVC line set tape, available in a variety of colors, used for general purpose floor, lane and aisle marking, color-coding and identification applications, as well as in the HVAC industry to wrap line sets, seam closed cell sponge insulation, and insulate air ducts and underground pipes. VP 410 is engineered with a non-corrosive adhesive and flexible backing; can be used in extensive temperature, moisture and humid conditions; and meets OSHA color-coding requirements.



VP 415



A SPVC film warning stripe tape used for lane marking and identification of safety zones and hazard areas. VP 415 is constructed with a flexible backing that is resistant to abrasion, UV light, acid, alkalides, oils, moisture, humidity and corrosion, and meets OSHA requirements for hazard markings.



HP 100®



General purpose grade, 1.6 mil, hot melt packaging tape for sealing lightweight boxes. HP 100® is engineered with an aggressive, high-tack adhesive and excellent holding power to keep carton seals intact.

HP 200®



Production grade, 1.8 mil, hot melt packaging tape for sealing medium-weight boxes. HP 200® is engineered with an aggressive, high-tack adhesive and excellent holding power to deliver secure carton seals.

GS 490



Economy grade, 100 lb., fiberglass reinforced strapping tape for light duty strapping, packaging, bundling and palletizing applications. GS 490 offers good adhesion, quick stick and shock resistance for a range of tasks.

