



Performance Masking Tapes

Prep for Perfection®

FrogTape® Performance Masking Tapes are perfect for marine, automotive, transportation and other applications where industrial coatings are applied. Offering a combination of conformability, durability and clean removability, these tapes are engineered to adhere to multiple surfaces and substrates and stand up against solvents, gel coats, scuffing, abuse – even high temperatures and bake cycles for up to 30 minutes. When the job is done, these tapes remove cleanly and easily from even the most critical industrial masking applications, delivering consistent paint lines and professional results.

FrogTape® Performance Masking Tapes:
The only thing they won't mask is your craftsmanship.



DOES NOT
contain
PaintBlock®
Technology



Performance Masking Tapes

FrogTape® 225 Gold



DOES NOT
contain
PaintBlock®
Technology



Performance grade, medium-high adhesion masking tape for use in moderate temperatures up to 225 F (for up to 30 minutes).

FrogTape® 250 Light Blue



DOES NOT
contain
PaintBlock®
Technology



Performance grade, medium-high adhesion masking tape for use in moderate temperatures up to 250 F (for up to 30 minutes).

FrogTape® 325 Pink



DOES NOT
contain
PaintBlock®
Technology



Performance grade, medium-high adhesion masking tape for use in moderate temperatures up to 325 F (for up to 30 minutes), especially in applications that demand a highly durable solution.

For Fineline Edges

FrogTape® FLS 325 Yellow

Performance grade, low stretch PVC fineline masking tape that offers a tough, yet conformable, waterproof and solvent-resistant solution to deliver crisp, fineline edges without staining or ghosting.

DOES NOT
contain
PaintBlock®
Technology



FrogTape® FLC 280 Blue

Performance grade, highly conformable PVC fineline masking tape that offers a waterproof and solvent-resistant solution for crisp, fineline edges when compound and tight radius curves are needed.

DOES NOT
contain
PaintBlock®
Technology



Pick for Performance

	FrogTape® 225 Gold	FrogTape® 250 Light Blue	FrogTape® 325 Pink	FrogTape® FLS 325 Yellow	FrogTape® FLC 280 Blue
Shurtape Product Type	CP 225 Gold	CP 250 Light Blue	CP 325 Pink	FLS 325 Yellow	FLC 280 Blue
Backing	Fine Structured Crepe	Fine Structured Crepe	Fine Structured Crepe	PVC	PVC
Adhesion	Medium-High	Medium-High	Medium-High	Medium	Medium
Service Temperature (Max)	225 F (30 Min)	250 F (30 Min)	325 F (30 Min)	325 F (45 Min)	280 F (45 Min)
Conformability	X	X			X
Straight Line Performance	X	X	X	X	
Solvent- and Gel Coat-Resistant	X	X	X	X	X
Moisture-Resistant	X	X	X	X	X
UV-Resistant (3 Days)	X	X	X		
Maximum Durability		X	X		
Clean Removability	X	X	X	X	X
Consistent Paint Lines	X	X	X	X	X
General MRO Applications	X	X	X		
Automotive Aftermarket	X	X		X	X
Marine OEM/Repair	X	X		X	X
Bus/RV	X	X		X	X
Heavy Equipment		X	X		