



Repair Tape Guide

Tape Grade						
	Duct Tape	Brute Force	Waterproof & Repair Flex-To-Fit	Waterproof & Repair Extreme	Clear Repair Tape	Super Glue Tape
Tape Thickness	16 mils	17 mils	10 mils	29 mils	7 mils	7.5 mils
Backing	PE Film w/Cloth	PE Film w/Cloth	Polyolefin Film	Polyolefin Film	Ionomer Film	Polyester Film
Adhesive	Natural Rubber	Natural Rubber	UV Acrylic	Butyl Rubber	Acrylic	Acrylic
Application Temps	35 F to 100 F	35 F to 100 F	0 F to 120 F	50 F to 100 F	10 F to 120 F	0 F to 175 F
Service Temps	32 F to 200 F	32 F to 200 F	-40 F to 240 F	23 F to 140 F	-5 F to 150 F	50 F to 100 F
UV Resistant			✓	✓	✓	
Works Under Water			✓	✓		
Tear By Hand	✓				✓	✓
UL 723 Certified	✓	✓	✓			
Applications	Bundle, support or haul heavy loads & seaming projects	Lifting, hauling & securing very heavy loads	Stretch & conform around small objects for a water-tight seal	Patch & repair large objects for a water-tight seal in extreme conditions	Discreet repairs on clear surfaces such as glass, screens or automobiles	Double-sided, alternative to glue and fasteners for quick fixes
Colors	Silver, Black, White, Neon	Black	White, Black, Clear	Black	Clear	Clear