

CP 150



CP 150 / 8-DAY PAINTER'S MATE GREEN® BRAND PAINTER'S TAPE - MULTI-SURFACE

TYPICAL APPLICATIONS

- For interior use on painted walls, woodwork, glass, metal and vinyl

PRODUCT FEATURES

- Painter's Mate Green® brand painter's tape
- Medium adhesion
- Conforms well to curved or uneven surfaces
- UV-resistant
- Delivers professional results

CONSTRUCTION

Backing: Crepe paper

Adhesive: Synthetic rubber-based adhesive

STANDARD WIDTHS

0.94 in; 1.41 in; 1.88 in; 2.83 in

24 mm; 36 mm; 48 mm; 72 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type I

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment.

Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Backing	8 oz/in width	0.8 N/10 mm
Adhesion to Stainless Steel	30 oz/in width	3.28 N/10 mm
Elongation	10%	10%
Service Temperature Range	NA to 150 F	NA to 66 C
Tensile	21 lbs/in width	36.8 N/10 mm
Thickness	4.6 mils	0.12 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

