

CP 743 SPECIALTY GRADE, PHOTOGRAPHIC BLACK MASKING TAPE

TYPICAL APPLICATIONS

- For use in photo studios, film processing labs and home darkrooms
- Recommended for use as a chart tape
- Used for quality photographic reproduction work, including cropping and edging negatives for contact printing
- Also used for sealing camera bellows and film holders against light leaks

PRODUCT FEATURES

- Specialty grade photographic black masking tape
- Very high adhesion
- Light-free masking
- Good quick stick
- Highly conformable

CONSTRUCTION

Backing: Impregnated paper

Adhesive: Rubber-based adhesive

STANDARD WIDTHS

0.94 in; 1.41 in; 1.88 in

24 mm; 36 mm; 48 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type I

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Service Temperature Range

Tensile

Thickness

STANDARD

47 oz/in width

8%

45 F to 150 F

24 lbs/in width

6.5 mils

METRIC

5.14 N/10 mm

8%

7 C to 66 C

42.0 N/10 mm

0.17 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

