

CT 109 GENERAL PURPOSE GRADE TRANSPARENT CELLULOSE FILM TAPE

TYPICAL APPLICATIONS

- For sealing, packaging and mending applications, particularly involving hard-to-stick-to surfaces
- Also used for splicing applications

PRODUCT FEATURES

- General purpose transparent cellulose film tape
- Adheres to hard-to-stick-to surfaces
- High tensile strength
- Hand-tearable
- Static-free in accordance with Afera Test Method 4011 - "Electric Strength of Adhesive Tape"

CONSTRUCTION

Backing: Transparent, hand-tearable, cellulose film

Adhesive: Rubber-based adhesive

STANDARD WIDTH

0.7 in

18 mm

STANDARD LENGTH

72 yd

66 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

CID A-A-113D, Type I, Class A

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Service Temperature Range

Tensile

Thickness

STANDARD

35 oz/in width

18%

NA to 265 F

22 lbs/in width

1.7 mils

METRIC

3.83 N/10 mm

18%

NA to 129 C

38.5 N/10 mm

0.043 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

