

DF 65 GENERAL PURPOSE GRADE DOUBLE-COATED FLAT PAPER TAPE

TYPICAL APPLICATIONS

- For mounting, holding, splicing, tabbing and fastening applications that demand aggressive adhesion

PRODUCT FEATURES

- General purpose grade double-coated flat paper tape
- Good tensile strength
- Superior adhesion to a variety of substrates
- Wrinkle-resistant tape and liner
- Hand-tearable

CONSTRUCTION

Backing: Flat paper

Adhesive: Rubber-based adhesive

Liner: Non-contaminating, siliconized, flat paper release liner

STANDARD WIDTHS

0.5 in; 0.94 in; 1.41 in; 1.88 in; 2.83 in

18 mm; 24 mm; 36 mm; 48 mm; 72 mm

STANDARD LENGTH

36 yd

33 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in


APPLICABLE STANDARDS

CID A-A-180C, Type II, Grade B

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Service Temperature Range

Tensile

Thickness - Without Liner

STANDARD

65 oz/in width

3%

50 F to 225 F

33 lbs/in width

5.0 mils

METRIC

7.11 N/10 mm

3%

10 C to 107 C

57.8 N/10 mm

0.13 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

