

DF 164 DOUBLE-COATED PE FOAM TAPE

TYPICAL APPLICATIONS

- For bonding to most surfaces including low-surface energy materials like PE and PP, vibration reduction, and sound damping

PRODUCT FEATURES

- Superior adhesion to a variety of surfaces, including low-surface energy materials like PE and PP
- Excellent conformability
- Good moisture resistance

CONSTRUCTION

Backing: 1/16 in closed cell polyethylene foam

Adhesive: Rubber-based adhesive

Liner: 83-lb. white super calendered kraft

STANDARD WIDTHS

0.47 in; 0.7 in; 0.94 in
12 mm; 19 mm; 24 mm

STANDARD LENGTH

36 yd
33 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	137 oz/in width	14.99 N/10 mm
Application Temperature Range	50F to 180F	10C to 82C
Elongation	339%	339%
Service Temperature Range	0 F to 180 F	-18 C to 82 C
Tensile	145 lbs/in width	253.9 N/10 mm
Thickness	70.5 mils	1.79 mm
Thickness - Without Liner	66.1 mil	1.68 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

