

DF 545 Duck Pro® by Shurtape®



DF 545 DUCK PRO® BY SHURTAPE® PROFESSIONAL GRADE, PREMIUM DOUBLE-COATED CLOTH TAPE

TYPICAL APPLICATIONS

- For securing carpet and pad at convention centers, arenas and hotels
- Can also be used for general purpose hanging applications in the construction and abatement industries
- Can also be used for splicing applications

PRODUCT FEATURES

- Professional grade, premium performance double-coated cloth tape
- Excellent adhesion to smooth and irregular surfaces
- High tensile strength
- Easy to unwind
- 30-day indoor, residue-free removal

CONSTRUCTION

Backing: Polyester/cotton blend cloth

Adhesive: Rubber-based adhesive

Liner: Siliconized, polyethylene release liner

STANDARD WIDTH

1.88 in

48 mm

STANDARD LENGTH

36.1 yd

33 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

ASTM D-4236

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants. To remove the blue liner, use scissors, a knife or blade to cut a small slit in the tape at the desired length. Then, hand tear the rest of the tape for easy liner separation.

COLOR



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel - Exposed Side	52 oz/in width	5.69 N/10 mm
Adhesion to Stainless Steel - Liner Side	64 oz/in width	7.0 N/10 mm
Elongation	8%	8%
Service Temperature Range	50 F to 200 F	10 C to 93 C
Tensile	24 lbs/in width	42.0 N/10 mm
Thickness - Nominal	10.5 mils	0.27 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



*To remove the blue liner, use scissors, a knife or blade to cut a small slit in the tape at the desired length. Then, hand tear the rest of the tape for easy liner separation.



Shurtape Technologies, LLC | PO BOX 1530 Hickory, NC 28603-1530 USA | Phone 1.888.442.TAPE (8273) | Fax 800.335.7651 | shurtapetech.com
ISO 9001 CERTIFIED QUALITY SYSTEM
Shurtape is a registered trademark of Shurtape Technologies, LLC Form# TDS-DF-545-Duck-Pro-by-Shurtape-20240610