

DT 200 PREMIUM PERFORMANCE GRADE DOUBLE-COATED NONWOVEN TISSUE TAPE

TYPICAL APPLICATIONS

- For high-speed splicing in the corrugated cardboard production process in temperatures up to 400 F
- Can also be used as a mounting and laminating system for irregularly shaped metals, foams, foils and nameplates
- For manual applications

PRODUCT FEATURES

- Premium performance grade double-coated nonwoven tissue tape
- High adhesion and quick stick
- Superior temperature resistance up to 400 F
- Excellent conformability to irregular surfaces
- Hand-tearable

CONSTRUCTION

Backing: Nonwoven tissue

Adhesive: Solvent-based acrylic adhesive

Liner: White glassine liner

STANDARD WIDTHS

0.47 in; 0.7 in; 0.94 in; 1.41 in; 1.88 in; 2.83 in
12 mm; 18 mm; 24 mm; 36 mm; 48 mm; 72 mm

STANDARD LENGTH

54.6 yd
50 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in


APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	55 oz/in width	6.02 N/10 mm
Elongation	3.5%	3.5%
Service Temperature Range	-20 F to 212 F	-29 C to 100 C
Tensile	6.3 lbs/in width	11.0 N/10 mm
Thickness - With Liner	7.0 mils	0.18 mm
Thickness - Without Liner	4.5 mils	0.11 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

