

FP 96 PACKAGING GRADE FLATBACK KRAFT PAPER TAPE

TYPICAL APPLICATIONS

- For hand and machine carton sealing
- Also used for splicing various substrates
- Also used for general purpose packaging, binding, holding, tabbing, reinforcing, banding and patching applications

PRODUCT FEATURES

- Packaging grade flatback paper tape
- Very high adhesion
- High cross-directional strength
- Resistant to curling, abrasion, water, solvents and oil
- Can be used for "shingling" (tape-on-tape)

CONSTRUCTION

Backing: Extensible, kraft, flatback paper

Adhesive: Rubber-based adhesive

STANDARD WIDTHS

1.88 in; 2.83 in

48 mm; 72 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type II

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



Kraft
(KFT)

PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Service Temperature Range

Tensile

Thickness

STANDARD

90 oz/in width

6%

50 F to 150 F

36 lbs/in width

6.1 mils

METRIC

9.85 N/10 mm

6%

10 C to 66 C

63.0 N/10 mm

0.15 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

