

FP 97 GENERAL PURPOSE GRADE FLATBACK KRAFT PAPER TAPE

TYPICAL APPLICATIONS

- For hand and machine carton sealing
- Also used for splicing various substrates
- Also used for general purpose packaging, binding, holding, tabbing, reinforcing, banding and patching applications
- Can also be used in floor seaming applications

PRODUCT FEATURES

- General purpose grade flatback paper tape
- Very high adhesion
- Excellent quick stick and holding power
- High cross-directional strength
- Resistant to curling, abrasion and water

CONSTRUCTION

Backing: Extensible, kraft, flatback paper

Adhesive: Synthetic rubber-based adhesive

STANDARD WIDTHS

0.94 in; 1.88 in; 2.83 in
24 mm; 48 mm; 72 mm

STANDARD LENGTH

60.1 yd
55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type II
FDA Indirect Contact CFR 21, 174.5
FDA Indirect Contact CFR 21, 175.105
FDA Indirect Contact CFR 21, 176.170
FDA Indirect Contact CFR 21, 176.180

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	110 oz/in width	12.04 N/10 mm
Elongation	6%	6%
Service Temperature Range	60 F to 150 F	16 C to 66 C
Tensile	35 lbs/in width	61.3 N/10 mm
Thickness	6.0 mils	0.15 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

