

FP 115 HIGH PERFORMANCE GRADE FLATBACK KRAFT PAPER TAPE

TYPICAL APPLICATIONS

- For industrial splicing, start-up, tabbing, shingling and overlapping applications
- Effectively secures the paper to the core during roll start-up, holds the splice during processing and anchors the end of the roll securely
- Also ideal for tasks in which the tape must stick well to itself, including shingling and overlapping applications

PRODUCT FEATURES

- High performance grade flatback paper tape
- Very high adhesion
- Quick bond and strong hold to smooth and porous papers, including 100 percent recycled paper
- Easy to start-up and unwind
- Resistant to moisture and humidity, which prevents the tape from lifting, puckering and curling

CONSTRUCTION

Backing: Flatback kraft paper

Adhesive: Synthetic rubber-based adhesive

STANDARD WIDTHS

1.88 in; 2.83 in; 3.77 in; 0.94 in
24 mm; 48 mm; 72 mm; 96 mm

STANDARD LENGTH

60.1 yd
55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type II

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

Adhesion to Stainless Steel
Elongation
Service Temperature Range
Tensile
Thickness

STANDARD

70 oz/in width
3%
NA to 120 F
40 lbs/in width
6.5 mils

METRIC

7.66 N/10 mm
3%
NA to 49 C
70.1 N/10 mm
0.17 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

