

FP 202 PACKAGING PREMIUM GRADE BLEACHED FLATBACK PAPER TAPE

TYPICAL APPLICATIONS

- For splicing various substrates
- Also used for heavy duty hand and machine carton sealing applications
- Also used for general purpose applications where a thick, flatback paper tape is required

PRODUCT FEATURES

- Packaging premium grade flatback paper tape
- Very high adhesion
- Excellent quick stick
- Resistant to abrasion, water, solvents and oil

CONSTRUCTION

Backing: Heavy duty bleached flatback paper

Adhesive: Rubber-based adhesive

STANDARD WIDTHS

1.88 in; 2.83 in

48 mm; 72 mm

STANDARD LENGTHS

60.1 yd, 120.2 yd

55 m, 110 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type II

ASTM D 5486M-12, Type V

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



Natural
(NAT)

PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Service Temperature Range

Tensile

Thickness

STANDARD

56 oz/in width

3%

50 F to 180 F

55 lbs/in width

7.5 mils

METRIC

6.13 N/10 mm

3%

10 C to 82 C

96.3 N/10 mm

0.19 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

