

FP 227 PRINTABLE, HIGH ADHESION COLORED FLATBACK PAPER TAPE

TYPICAL APPLICATIONS

- For full-web flexographic printing equipment or hand-labeling applications

PRODUCT FEATURES

- Printable flatback paper tape
- High adhesion
- Flexible
- Abrasion- and oil-resistant
- Available in a variety of colors, including high-visibility fluorescents

CONSTRUCTION

Backing: Colored flatback paper

Adhesive: Rubber-based adhesive

STANDARD WIDTHS

0.94 in; 1.88 in; 2.83 in; 6 in

24 mm; 48 mm; 72 mm; 152 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type II


All colors except fluorescent conform to ASTM D-4236

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment.

Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	57 oz/in width	6.24 N/10 mm
Elongation	2.50%	2.50%
Service Temperature Range	40 F to 150 F	4 C to 66 C
Tensile	30 lbs/in width	52.5 N/10 mm
Thickness	6.4 mils	0.16 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

