

GG 200 DOUBLE-COATED CREPE PAPER GOLF GRIP TAPE

TYPICAL APPLICATIONS

- For factory and clubhouse golf grip installation
- Can also be used for mounting, holding, splicing, tabbing and fastening a variety of substrates when an aggressive, double-sided tape is required

PRODUCT FEATURES

- Double-coated crepe paper golf grip tape
- Fast set-up and easy clean-up
- Good tensile strength
- Superior adhesion to a variety of substrates
- Wrinkle-resistant tape and liner

CONSTRUCTION

Backing: Crepe paper

Adhesive: Rubber-based adhesive

Liner: Non-contaminating, siliconized, crepe paper release liner

STANDARD WIDTHS

0.94 in; 1.88 in

24 mm; 48 mm

STANDARD LENGTH

36 yd

33 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



Natural
(NAT)

PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Service Temperature Range

Tensile

Thickness - Without Liner

STANDARD

50 oz/in width

10%

50 F to 150 F

23 lbs/in width

6.5 mils

METRIC

5.47 N/10 mm

10%

10 C to 66 C

40.3 N/10 mm

0.17 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

