

HP 260 SURFACE PRINTABLE, PRODUCTION GRADE HOT MELT PACKAGING TAPE

TYPICAL APPLICATIONS

- For use on Siat L33, L36, L233 (or equivalent) surface printing presses
- For manual sealing of medium-weight cartons in normal manufacturing and shipping environments
- May also be used in automated industrial carton sealing applications

PRODUCT FEATURES

- Production grade, medium duty packaging tape
- Surface printable with leading brands of solvent inks
- Instant, permanent bond to a wide range of substrates and surfaces
- Special release coating for consistent, low force unwind off the roll

CONSTRUCTION

Backing: Directly printable, 30 micron biaxially oriented polypropylene cast film

Adhesive: Synthetic rubber/resin hot melt adhesive

STANDARD WIDTHS

5.66 in; 11.96 in; 11.33 in
144 mm; 150 mm; 288 mm

STANDARD LENGTHS

1000 yd, 1500 yd, 2000 yd
914 m, 1371 m, 1828 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

ASTM D 1974/D 1974M-22
CID A-A-1684C
FDA Indirect Contact CFR 21, 175.105

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Backing	4 oz/in width	0.44 N/10 mm
Adhesion to Stainless Steel	44 oz/in width	4.82 N/10 mm
Application Temperature Range	35 F to 110 F	2 C to 43 C
Elongation	150%	150%
Holding Power to Fiberboard	15,000 minutes	15,000 minutes
Service Temperature Range	-20 F to 150 F	-29 C to 66 C
Tensile Strength - Longitudinal Direction	27 lbs/in width	47.3 N/10 mm
Tensile Strength - Transverse Direction	44 lbs/in width	77.1 N/10 mm
Thickness	1.9 mils	0.048 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

