

HP 350 CUSTOM-PRINTED, PERFORMANCE GRADE HOT MELT PACKAGING TAPE

TYPICAL APPLICATIONS

- Custom-printed to prevent pilferage and allow personalization of outgoing cartons
- For critical closure manual or automated industrial carton sealing of medium-weight cartons that are subjected to increased handling stress

PRODUCT FEATURES

- Performance purpose grade, critical closure, medium duty packaging tape
- Custom-printed for personalization
- Extra high bonding strength and holding power for a long-lasting, secure seal
- Instant, permanent bond to a wide range of substrates and surfaces
- Special release coating for consistent, low force unwind off the roll
- Performs reliably to the core for efficient tape consumption
- For hand use or automated applications

CONSTRUCTION

Backing: 35 micron biaxially oriented polypropylene cast film

Adhesive: Synthetic rubber/resin hot melt adhesive

STANDARD WIDTHS

1.88 in; 2.83 in
48 mm; 72 mm

STANDARD LENGTHS

109.3 yd, 100 yd
100 m, 914 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

ASTM D 1974/D 1974M-22
CID A-A-1684C
FDA Indirect Contact CFR 21, 175.105

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Backing	5 oz/in width	0.55 N/10 mm
Adhesion to Stainless Steel	50 oz/in width	5.47 N/10 mm
Application Temperature Range	35 F to 110 F	2 C to 43 C
Elongation	150%	150%
Holding Power to Fiberboard	25,000 minutes	25,000 minutes
Service Temperature Range	-20 F to 150 F	-29 C to 66 C
Tensile Strength - Longitudinal Direction	30 lbs/in width	52.5 N/10 mm
Tensile Strength - Transverse Direction	55 lbs/in width	96.3 N/10 mm
Thickness	2.2 mils	0.056 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

