

MJ 100 FIBERGLASS MESH TAPE

TYPICAL APPLICATIONS

- For reinforcing joints, seams and connections when paint-on mastic is used in HVAC applications
- Can also be applied to drywall seams before the application of joint compound

PRODUCT FEATURES

- Professional grade open weave fiberglass mesh drywall tape
- Self-adhering
- Light adhesive on one side for non-slipping
- Width selection provides ample support for mastic coat
- Fabric count - 8 ends by 8 picks for superior strength

CONSTRUCTION

Backing: Fiberglass mesh

Adhesive: Water-based acrylic adhesive

STANDARD WIDTHS

1.88 in; 3 in

48 mm; 76.2 mm

STANDARD LENGTH

150 ft

45.72 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in


APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Tensile

Thickness

STANDARD

8 oz/in width

3.83%

75.5 lbs/in width

9.0 mils

METRIC

0.88 N/10 mm

3.83%

132.2 N/10 mm

0.23 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

