

P- 672 PREMIUM GRADE, LIGHT DUTY GAFFER'S TAPE

TYPICAL APPLICATIONS

- For sealing containers and protection from welding splatter
- Can also be used for sealing rooms, abrasion protection, general holding, bundling and temporary repair applications. Meets water leachable requirements for detrimental elements (FI & BR <250PPM; S & C <500PPM) in accordance with MIL-STD-2041.

PRODUCT FEATURES

- Premium grade gaffer's tape
- High tensile strength
- Abrasion-resistant
- Hand-tearable in machine and cross directions

CONSTRUCTION

Backing: Matte-finish coated cloth

Adhesive: Synthetic rubber adhesive

STANDARD WIDTHS

0.94 in; 1.88 in; 2.83 in

24 mm; 48 mm; 72 mm

STANDARD LENGTH

50 yd

46 m

Not all widths are available in all colors. Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS


CID A-A-1586A

MIL-STD-2041

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	77 oz/in width	8.43 N/10 mm
Elongation	6%	6%
Service Temperature Range	50 F to 180 F	10 C to 82 C
Tensile	70 lbs/in width	122.6 N/10 mm
Thickness	12.0 mils	0.30 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

