

PC 608 Duck Pro® by Shurtape®



PC 608 DUCK PRO® BY SHURTAPE® GENERAL PURPOSE GRADE, CO-EXTRUDED ABATEMENT DUCT TAPE

TYPICAL APPLICATIONS

- For use when building containments and a variety of other applications in remediation, restoration and abatement jobs
- Can be used for mold and asbestos removal

PRODUCT FEATURES

- General purpose grade, co-extruded poly-hanging duct tape
- High tack
- Excellent holding power with good conformability
- Cold-temperature adhesion
- Easy to unwind and tear

CONSTRUCTION

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Blended rubber adhesive

STANDARD WIDTHS

1.88 in; 2.83 in

48 mm; 72 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

Tested in accordance with UL 723

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Service Temperature Range

Tensile

Thickness - Nominal

STANDARD

75 oz/in width

20%

35 F to 200 F

26 lbs/in width

9.0 mils

METRIC

8.21 N/10 mm

20%

2 C to 93 C

45.5 N/10 mm

0.23 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

