

PC 610 PERFORMANCE GRADE CLOTH ABATEMENT DUCT TAPE

TYPICAL APPLICATIONS

- For sealing walls, doors and windows in abatement applications
- Ideal for use on rugged jobs in warm and cold climates, as well as dry and wet environments

PRODUCT FEATURES

- Performance grade abatement tape
- Excellent cold temperature adhesion
- Superior holding power to poly-sheeting, metal and unpainted wood
- Easy to unwind and tear
- Will not twist or curl during application

CONSTRUCTION

Backing: Polyethylene film with a cloth carrier

Adhesive: Blended rubber adhesive

STANDARD WIDTH

1.88 in

48 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



**Metallic
Silver
(MSL)**

PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Service Temperature Range

Tensile

Thickness - Nominal

STANDARD

61 oz/in width

26%

25 F to 200 F

26 lbs/in width

10.0 mils

METRIC

6.68 N/10 mm

26%

-4 C to 93 C

45.5 N/10 mm

0.25 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

