

PC 619 Duck Pro® by Shurtape®



PC 619 DUCK PRO® BY SHURTAPE® GENERAL PURPOSE GRADE, SPECIALTY GRADE, FLUORESCENT CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- For general use, including color-coding, labeling, floor marking and book-binding
- Also used for stage preparation in the motion picture and audio/visual industries
- Can also be used for a variety of applications in the hospitality, motorsports and floral industries

PRODUCT FEATURES

- General purpose, specialty grade duct tape
- Indoor use
- Conformable
- Easy to unwind and tear
- Waterproof backing
- Color-coding and labeling
- Great for temporary indoor floor marking and removes cleanly from most surfaces for up to 3 weeks. Not recommended for hardwood floors or in direct sunlight

CONSTRUCTION

Backing: Polyethylene film with a cloth carrier

Adhesive: Natural rubber adhesive

STANDARD WIDTHS

1.88 in; 2.83 in

48 mm; 72 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in


APPLICABLE STANDARDS

ASTM D-4236

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	70 oz/in width	7.66 N/10 mm
Elongation	20%	20%
Service Temperature Range	40 F to 200 F	4 C to 93 C
Tensile	26 lbs/in width	45.5 N/10 mm
Thickness - Nominal	9.0 mils	0.23 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

