

PC 667 SPECIALTY GRADE, OUTDOOR STUCCO DUCT TAPE

TYPICAL APPLICATIONS

- For protective masking of non-painted surfaces, including steel, vinyl, aluminum and anodized metals
- Use in plastering, stucco, concrete, pool and tile applications
- For protecting window and door frames during stucco applications

PRODUCT FEATURES

- Specialty grade, outdoor cloth duct tape
- 14-day UV-resistant
- Easy to tear
- Removes cleanly
- Waterproof backing

CONSTRUCTION

Backing: Waterproof, UV-resistant polyethylene film with a cloth carrier

Adhesive: Blended rubber adhesive

STANDARD WIDTH

1.88 in
48 mm

STANDARD LENGTH

60.1 yd
55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in


APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	40 oz/in width	4.38 N/10 mm
Elongation	22%	22%
Service Temperature Range	50 F to 200 F	10 C to 93 C
Tensile	26 lbs/in width	45.5 N/10 mm
Thickness - Nominal	9.0 mil	0.23 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

