

PC 769 Duck Pro® by Shurtape®



PC 769 DUCK PRO® BY SHURTAPE® PROFESSIONAL GRADE, CLEAN REMOVAL, CO-EXTRUDED DUCT TAPE

TYPICAL APPLICATIONS

- For use in for a variety of indoor and outdoor clean-removal projects such as holding cords, bundling and repair projects

PRODUCT FEATURES

- Professional grade, clean removal, co-extruded duct tape
- Easy to unwind and tear
- Indoor clean removal up to six months
- Waterproof backing
- UV-resistant

CONSTRUCTION

Backing: Polyethylene film with a cloth carrier

Adhesive: Natural rubber adhesive

STANDARD WIDTHS

1.88 in; 2.83 in

48 mm; 72 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment.

Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Service Temperature Range

Tensile

Thickness - Nominal

STANDARD

55 oz/in width

24%

50 F to 200 F

24 lbs/in width

12.2 mils

METRIC

6.02 N/10 mm

24%

10 C to 93 C

42 N/10 mm

0.31 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

