

PC 857 UL 181B-FX LISTED/PRINTED CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- Used in the HVAC industry to seal, seam and join Class 1 Flex Duct

PRODUCT FEATURES

- Printed cloth duct tape
- UL 181B-FX Listed - clearly printed on the tape for quick identification
- High holding power
- Superior shear strength
- Easy to tear

CONSTRUCTION

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Blended rubber adhesive

STANDARD WIDTHS

1.88 in; 2.83 in

48 mm; 72 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

UL 181B-FX

UL Listed

Tested in accordance with UL 723

FSI 15/SDI 30

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Service Temperature Range

Tensile

Thickness - Nominal

STANDARD

60 oz/in width

8%

50 F to 212 F

27 lbs/in width

14.0 mils

METRIC

6.57 N/10 mm

8%

10 C to 100 C

47.3 N/10 mm

0.36 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

