

PC 9 DUCK PRO® BY SHURTAPE® GENERAL PURPOSE GRADE, CO-EXTRUDED CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- A good choice for general purpose use in bundling, sealing, repairing and holding
- Use for color-coding, labeling or match to a surface for a discreet fix
- Hangs and holds light-weight, polyethylene sheeting
- For permanent or temporary use
- Great for temporary indoor floor marking projects. Not recommended for hardwood floors or in direct sunlight

PRODUCT FEATURES

- General purpose, performance grade duct tape
- Made using Polybonded CO-EX Technology® that prevents delamination
- Good conformability, easy to unwind & tear
- Will not twist or curl during application
- All-weather performance with water-resistant backing
- Offers 30-day indoor clean removal on most surfaces without leaving residue
- Adheres to various surfaces such as metal, glass, plastic and cement

CONSTRUCTION

Backing: Polyethylene film with a cloth carrier

Adhesive: Natural rubber adhesive

STANDARD WIDTHS

1.88 in; 2.83 in

48 mm; 72 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

Tested in accordance with UL 723

ASTM D-4236

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	80 oz/in width	8.76 N/10 mm
Elongation	20%	20%
Service Temperature Range	35 F to 200 F	2 C to 93 C
Tensile	26 lbs/in width	45.5 N/10 mm
Thickness - Nominal	9.0 mils	0.23 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

