

PE 333 NON-UV-RESISTANT POLYETHYLENE TAPE

TYPICAL APPLICATIONS

- For masking surfaces, such as windows and doors, during stucco application and painting
- Can also be used for masking curved surfaces
- Also used for seaming underslab vapor barriers
- Used in the abatement, restoration and remodeling industries to hold poly-sheeting when building containments
- Used to reinforce boat shrink wrap seams to create a tight, continuous seal for tenting of vessel during seasonal storage.

PRODUCT FEATURES

- Non-UV-resistant polyethylene film tape
- Excellent conformability
- Maintains a watertight seal
- Removes cleanly

CONSTRUCTION

Backing: Polyethylene film

Adhesive: Synthetic rubber adhesive

STANDARD WIDTHS

1.88 in; 2.83 in; 3.77 in
48 mm; 72 mm; 96 mm

STANDARD LENGTH

60.1 yd
55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in


APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	70 oz/in width	7.66 N/10 mm
Elongation	80%	80%
Service Temperature Range	32 F to 160 F	0 C to 71 C
Tensile	19 lbs/in width	33.3 N/10 mm
Thickness	7.0 mils	0.18 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

