

PE 555 UV-RESISTANT, WATERPROOF STUCCO MASKING TAPE

TYPICAL APPLICATIONS

- For masking surfaces during stucco application and painting
- Can also be used for surface protection, color-coding, splicing and seaming on pipe-fitting covers

PRODUCT FEATURES

- UV-resistant polyethylene film tape
- Excellent adhesion and tearability
- Removes cleanly
- Waterproof

CONSTRUCTION

Backing: Red polyethylene film

Adhesive: Synthetic rubber adhesive

STANDARD WIDTH

1.88 in

48 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Service Temperature Range

Tensile

Thickness

STANDARD

92 oz/in width

94%

32 F to 160 F

27 lbs/in width

9.0 mils

METRIC

10.07 N/10 mm

94%

0 C to 71 C

47.3 N/10 mm

0.23 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

