

PP 807 PREMIUM GRADE SOLVENT-BASED ACRYLIC GENERAL PURPOSE AND LABEL PROTECTION TAPE

TYPICAL APPLICATIONS

- For moisture-proof protection of labels and handling instructions
- Also used for industrial and production laminating, joining, covering and protecting jobs

PRODUCT FEATURES

- Premium grade general purpose and label protection tape
- Provides moisture-proof seal with excellent visibility of information under the tape
- Resists bacteria, fungi, solvents and weathering
- Will not discolor or crack
- Performs in a range of temperatures

CONSTRUCTION

Backing: 25 micron cast biaxially oriented polypropylene film

Adhesive: Solvent-based acrylic adhesive

STANDARD WIDTHS

4 in; 6 in

101.6 mm; 152.4 mm

STANDARD LENGTH

72 yd

66 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Backing	15 oz/in width	1.64 N/10 mm
Adhesion to Kraft	9 oz/in width	0.99 N/10 mm
Adhesion to Stainless Steel	23 oz/in width	2.52 N/10 mm
Application Temperature Range	20 F to 110 F	-7 C to 43 C
Elongation	140%	140%
Service Temperature Range	-20 F to 180 F	-29 C to 82 C
Tensile	20 lbs/in width	35.0 N/10 mm
Thickness	1.8 mils	0.046 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

