

PP 808 GENERAL PURPOSE GRADE UPVC FILM TAPE

TYPICAL APPLICATIONS

- For lightweight bag sealing, banding, bundling and packaging applications
- Also used for color-coding tasks

PRODUCT FEATURES

- General purpose grade UPVC film tape
- Moisture-resistant
- Performs in subfreezing temperatures

CONSTRUCTION

Backing: Unplasticized polyvinylchloride (UPVC) film

Adhesive: Natural rubber adhesive

STANDARD WIDTH

0.35 in

9 mm

STANDARD LENGTH

180.4 yd

165 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	24 oz/in width	2.63 N/10 mm
Application Temperature Range	20 F to 110 F	-7 C to 43 C
Elongation	60%	60%
Service Temperature Range	0 F to 150 F	-18 C to 66 C
Tensile	27 lbs/in width	47.3 N/10 mm
Thickness	2.1 mils	0.053 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

