

PP 810 PREMIUM GRADE SOLVENT-BASED ACRYLIC PACKAGING TAPE

TYPICAL APPLICATIONS

- For sealing light- to medium-weight cartons in everyday shipping and handling environments
- Also used for bundling and securing loose objects
- Can also be used to repair corrugated cartons, paper and film containers
- Use with a hand-held dispenser

PRODUCT FEATURES

- Premium grade, light/medium duty packaging tape
- Excellent adhesion and holding power to protect contents from pilferage
- Seals out moisture and dirt
- Performs in a range of temperatures

CONSTRUCTION

Backing: 25 micron cast biaxially oriented polypropylene film

Adhesive: Solvent-based acrylic adhesive

STANDARD WIDTHS

1.88 in; 2.83 in

48 mm; 72 mm

STANDARD LENGTHS

54.6 yd, 109.3 yd

50 m, 100 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

CID A-A-1684C

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Backing - Hand Rolls Only	16 oz/in width	1.75 N/10 mm
Adhesion to Kraft	10 oz/in width	1.09 N/10 mm
Adhesion to Stainless Steel	22 oz/in width	2.41 N/10 mm
Application Temperature Range	20 F to 110 F	-7 C to 43 C
Elongation	140%	140%
Service Temperature Range	-20 F to 180 F	-29 C to 82 C
Tensile	22 lbs/in width	38.5 N/10 mm
Thickness	1.8 mils	0.046 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

