

PP 815 HEAVY DUTY GRADE SOLVENT-BASED ACRYLIC PACKAGING TAPE

TYPICAL APPLICATIONS

- For critical sealing and repairing of corrugated containers in hot and cold environments
- Use with a hand-held dispenser

PRODUCT FEATURES

- Heavy duty grade packaging tape
- Excellent impact and shear resistance
- Performs in a range of temperatures
- Excellent aging characteristics

CONSTRUCTION

Backing: 40 micron cast biaxially oriented polypropylene film

Adhesive: Solvent-based acrylic adhesive

STANDARD WIDTH

1.88 in

48 mm

STANDARD LENGTH

54.6 yd

50 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

CID A-A-1684C

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



Clear
(CLR)

PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Backing - Hand Rolls Only	18 oz/in width	1.97 N/10 mm
Adhesion to Kraft	16 oz/in width	1.75 N/10 mm
Adhesion to Stainless Steel	28 oz/in width	3.06 N/10 mm
Application Temperature Range	20 F to 110 F	-7 C to 43 C
Elongation	140%	140%
Service Temperature Range	-20 F to 180 F	-29 C to 82 C
Tensile	26 lbs/in width	45.5 N/10 mm
Thickness	2.6 mils	0.066 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

