

SF 683 SHURFLEX® PRINTED METALIZED CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- For use in the HVAC industry for airtight and moisture-free seaming, connecting, splicing, patching and sealing of sheet metal and flex duct, insulation, rigid ductboards, air vents and fiber board

PRODUCT FEATURES

- ShurFLEX® HVAC printed professional grade metalized duct tape
- Designed to match sheet metal, flex duct and ductboard
- Flexible and conformable
- Easy to unwind and tear
- Will not twist or curl during application

CONSTRUCTION

Backing: Printed metalized waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber adhesive

STANDARD WIDTHS

1.88 in; 2.83 in

48 mm; 72 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

Tested in accordance with UL 723

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Service Temperature Range

Tensile

Thickness - Nominal

STANDARD

55 oz/in width

23%

50 F to 200 F

26 lbs/in width

10.0 mils

METRIC

6.02 N/10 mm

23%

10 C to 93 C

45.5 N/10 mm

0.25 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

