

TG 356 PREMIUM PERFORMANCE GRADE ADHESIVE TRANSFER TAPE

TYPICAL APPLICATIONS

- For mounting, holding, joining and splicing various substrates, including paper, cardboard, textiles, plastics, leather, wood, glass and painted surfaces
- For use on displays, POS, posters, etc.
- Use with an adhesive transfer gun to make almost any surface self-adhesive

PRODUCT FEATURES

- Premium performance grade adhesive transfer tape
- Eliminates the clean-up and drying time associated with liquid adhesives
- Maintains adhesion characteristics in normal and severe environmental conditions
- Extremely conformable
- Resists humidity, most solvents and UV light

CONSTRUCTION

Adhesive: Unsupported, permanent, dry acrylic-based adhesive

Liner: Non-contaminating, siliconized, tan, paper release liner

STANDARD WIDTHS

0.47 in; 0.75 in

12 mm; 19 mm

STANDARD LENGTH

36 yd

33 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

1 in

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment.

Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	32 oz/in width	3.50 N/10 mm
Service Temperature Range	-60 F to 250 F	-51 C to 121 C
Thickness - With Liner	5.5 mils	0.14 mm
Thickness - Without Liner	2.0 mils	0.05 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

