

VF 719 ECONOMY GRADE UPVC FILM TAPE

TYPICAL APPLICATIONS

- For use with a hand dispenser to seal cartons with recycled fiber content, heavy ink coverage or rough surfaces

PRODUCT FEATURES

- Economy grade UPVC film
- Performs when subfreezing temperatures and moisture are factors

CONSTRUCTION

Backing: Unplasticized polyvinylchloride (UPVC) film

Adhesive: Natural rubber adhesive

STANDARD WIDTH

1.88 in

48 mm

STANDARD LENGTH

54.6 yd

50 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

CID A-A1689B, Type II

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



Tan
(TAN)



Natural
(NAT)



White
(WHI)

PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Service Temperature Range

Tensile

Thickness

STANDARD

13 oz/in width

60%

0 F to 150 F

23 lbs/in width

1.9 mils

METRIC

1.42 N/10 mm

60%

-18 C to 66 C

40.3 N/10 mm

0.048 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

