

VP 415 WARNING STRIPE TAPE

TYPICAL APPLICATIONS

- For lane marking and identification of safety zones and hazard areas
- Flexible for marking around objects

PRODUCT FEATURES

- General purpose grade warning stripe tape
- Resistant to abrasion, UV light, acid, alkalides, oils, moisture, humidity and corrosion
- Meets OSHA requirements for hazard markings

CONSTRUCTION

Backing: Striped, stabilized, plasticized, soft polyvinylchloride film (SPVC)

Adhesive: Natural rubber adhesive

STANDARD WIDTH

1.96 in

50 mm

STANDARD LENGTH

36 yd

33 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

CID A-A-1689B, Type 1, Class 2

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Service Temperature Range

Tensile

Thickness

STANDARD

12 oz/in width

200%

20 F to 140 F

15 lbs/in width

6.6 mils

METRIC

1.31 N/10 mm

200%

-7 C to 60 C

26.3 N/10 mm

0.17 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

