

WP 150 ECONOMY GRADE, WATER ACTIVATED REINFORCED PAPER TAPE WITH CUSTOM PRINT

TYPICAL APPLICATIONS

- For sealing light- to medium-weight cartons up to 25 lbs with normal exposure to handling, shipping and load stress
- Custom-printed with logo or message for delivery of goods without pilferage

PRODUCT FEATURES

- Economy grade reinforced paper tape
- Excellent tensile strength
- Conformable
- Directly printable

CONSTRUCTION

Backing: Reinforced kraft paper, (MD) H110/(CD) G150 fiberglass

Adhesive: Water activated adhesive

STANDARD WIDTHS

2.75 in; 2.83 in; 2.99 in
70 mm; 72 mm; 76 mm

STANDARD LENGTHS

375 ft, 450 ft 500 ft
115 m, 138 m, 153 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

None


APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



PHYSICAL PROPERTIES

	STANDARD	METRIC
Application Temperature Range	33 F to 110 F	0.6 C to 43 C
Bottom Sheet - Weight	23 lbs	10.43 kg
CD Pattern	1-1-1	NA
CD Spacing	1.25 in	3.17 cm
CD Tensile Strength	25 lbs/in	43.8 N/10 mm
MD Pattern	1-1-1-1-1	1-1-1-1-1
MD Spacing	5/8 in	1.58 cm
MD Tensile Strength	55 lbs/in width	96.3 N/10 mm
Service Temperature Range	-20 F to 120 F	-29 C to 49 C
Thickness	5.0 mils	0.13 mm
Top Sheet - Weight	23 lbs	10.43 kg

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

