

## WP 250 PRODUCTION GRADE, WATER ACTIVATED REINFORCED PAPER TAPE WITH CUSTOM PRINT

### TYPICAL APPLICATIONS

- For sealing medium-weight cartons up to 35 lbs in normal manufacturing and shipping environments
- Ideal for single parcel shipments
- Custom-printed with logo or message for delivery of goods without pilferage

### PRODUCT FEATURES

- Production grade reinforced paper tape
- Directly printed with logo or custom message
- Excellent tensile strength
- Also available in WP 150, WP 350 and WP 450 grades

### CONSTRUCTION

Backing: Reinforced kraft paper, (MD) G75/(CD) G150 fiberglass  
Adhesive: Water activated adhesive

### STANDARD WIDTH

Contact your Shurtape sales representative for available widths

Contact your Shurtape sales representative for available widths

### STANDARD LENGTH

Contact your Shurtape sales representative for available lengths

Contact your Shurtape sales representative for available lengths

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

### STANDARD CORE SIZE

None


### APPLICABLE STANDARDS

NA

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLORS



### PHYSICAL PROPERTIES

|                               | STANDARD        | METRIC        |
|-------------------------------|-----------------|---------------|
| Application Temperature Range | 33 F to 110 F   | 0.6 C to 43 C |
| Bottom Sheet - Weight         | 23 lbs          | 10.43 kg      |
| CD Pattern                    | 1-1-1           | NA            |
| CD Spacing                    | 1.25 in         | 3.17 cm       |
| CD Tensile Strength           | 27 lbs/in       | 47.3 N/10 mm  |
| MD Pattern                    | 1-1-1-1-1       | 1-1-1-1-1     |
| MD Spacing                    | 1/2 in          | 1.27 cm       |
| MD Tensile Strength           | 60 lbs/in width | 105.1 N/10 mm |
| Service Temperature Range     | -20 F to 120 F  | -29 C to 49 C |
| Thickness                     | 6.75 mils       | 0.17 mm       |
| Top Sheet - Weight            | 23 lbs          | 10.43 kg      |

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

