

RAP 201 PRODUCTION GRADE 90% PCR RPET ACRYLIC PACKAGING TAPE

TYPICAL APPLICATIONS

- For manual or automated industrial carton sealing of medium weight cartons

PRODUCT FEATURES

- 90% post-consumer recycled 19 micron rPET film
- Recycled™ Series production grade, medium duty acrylic packaging tape
- Production grade, medium duty acrylic packaging tape
- UV-resistant
- Excellent aging characteristics
- Performs in a range of temperatures

CONSTRUCTION

Backing: 19 micron 90% Post-Consumer Recycled rPET film

Adhesive: Emulsion acrylic adhesive

STANDARD WIDTHS

1.88 in; 2.83 in

48 mm; 72 mm

STANDARD LENGTHS

109.3 yd, 1640 yd

100 m, 1500 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

FDA Indirect Contact CFR 21, 175.105

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	22 oz/in width	2.41 N/10 mm
Application Temperature Range	20 F to 110 F	-7 C to 43 C
Elongation	135%	135%
Service Temperature Range	-20 F to 180 F	-29 C to 82 C
Tensile Strength - Longitudinal Direction	23 lbs/in width	40.3 N/10 mm
Thickness	1.3 mils	0.03 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



*To learn more, visit Shurtape.com/RRQ.