

DC 181 UL 181B-FX LISTED/PRINTED FILM TAPE

TYPICAL APPLICATIONS

- For use on Class 1 Flex Duct for connecting, joining, sealing and patching flexible air ductwork

PRODUCT FEATURES

- UL 181B-FX Listed film tape
- Quick stick
- Excellent conformability to uneven surfaces
- Easy to unwind and tear
- Color matches flex duct

CONSTRUCTION

Backing: BOPP Film: Metalized Silver with Red Print / Black with White Print

Adhesive: High-tack, cold temperature acrylic adhesive

STANDARD WIDTHS

1.88 in; 2.83 in

48 mm; 72 mm

STANDARD LENGTH

120.2 yd

110 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

UL 181B-FX

UL Listed

FSI 25/SDI 50

Tested in accordance with UL 723

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	38 oz/in width	4.16 N/10 mm
Elongation	200%	200%
Service Temperature Range	-10 F to 210 F	-23 C to 99 C
Tensile	31 lbs/in width	54.3 N/10 mm
Thickness	2.7 mils	0.07 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

