

PW 100 CORROSION-RESISTANT PVC PIPE WRAP TAPE

TYPICAL APPLICATIONS

- For corrosion protection of under and above ground metal and plastic pipe installations

PRODUCT FEATURES

- General purpose grade PVC pipe wrap tape
- Resists corrosion, moisture, bacteria, fungus and abrasion
- UV-resistant
- Lead free
- Excellent conformability

CONSTRUCTION

Backing: 10 mil, PVC film

Adhesive: Non-corrosive, rubber-based adhesive

STANDARD WIDTH

2 in

50.8 mm

STANDARD LENGTH

33.3 yd

30.4 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

1.5 in

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Application Temperature Range

Dielectric Strength

Elongation

Service Temperature Range

Tensile

Thickness

STANDARD

20 oz/in width

14 F to 176 F

600 volts/mil

200%

32 F to 104 F

25 lbs/in width

10.0 mils

METRIC

2.19 N/10 mm

-10 C to 80 C

600 volts/mil

200%

0 C to 40 C

44 N/10 mm

0.25 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

