

STUCCO MASKING TAPES

Thorough preparation is a requirement of your job – it's what helps you leave your mark of excellence on a job well done. You demand a tape that's easy to apply, yet strong enough to stand up against the harsh scraping of your trowel. You don't have time to waste cleaning up residue left behind after the tape has been removed. It's why you count on the Shurtape® line of stucco masking tapes for your stucco work.

Shurtape stucco masking tapes are designed with you in mind. Engineered to meet the rigid requirements of stucco applications, our full range of stucco masking tapes provides a secure, watertight seal, no matter the surface you're masking. Conformable to vinyl trim work, doors, windows, garage doors and more, our tapes are highly visible, as well as easy to unwind and tear. When the work is done, our tapes release easily and cleanly, even after prolonged exposure to sunlight.

Whether you're using a one-, two- or three-step process, Shurtape offers a broad array of stucco masking tapes to fit your needs.



Shurtape®


TRUE TO YOUR WORK®

SHURTAPE.COM 1.888.442.TAPE

STUCCO MASKING TAPES

TECHNICAL SPECIFICATIONS

TECHNICAL SPECIFICATIONS		Adhesion to Stainless Steel	Thickness	Tensile Strength	Elongation	Service Temperature Range	Application Temperature Range
PC 622	 Premium grade cloth duct tape used for protecting window and door frames during stucco application, as well as for various applications in high performance motorsports and for heavy duty bundling, holding and splicing.	51 oz/in width	12.5 mils	45 lbs/in width	11%	50 F – 200 F	–
PC 667	 Specialty grade, outdoor cloth duct tape used for protective masking of non-painted surfaces, including steel, vinyl, aluminum and anodized metals, in plastering, stucco, concrete, pool and tile applications where UV resistance is required.	40 lbs/in width	9 mils	26 lbs/in width	22%	50 F – 200 F	–
PE 444	 UV-resistant polyethylene film tape used to mask surfaces, such as windows and doors, during stucco application and painting.	80 lbs/in width	7 mils	19 lbs/in width	76%	32 F – 160 F	–



LEARN MORE

SHURTAPE.COM
1.888.442.TAPE



Shurtape®
TRUE TO YOUR WORK®

ISO 9001 CERTIFIED QUALITY SYSTEM
Printed in USA on recycled paper. © Shurtape Technologies, LLC 2026/MMC 02112