

PC 609 DUCK PRO® PROFESSIONAL GRADE, CO-EXTRUDED COLD TEMPERATURE AND ABATEMENT DUCT TAPE

TYPICAL APPLICATIONS

- Repairing thermal insulation and sealing metal ductwork in HVAC applications
- Building containments and a variety of other applications in remediation, restoration and abatement jobs
- Hanging polyethylene sheeting on a variety of surfaces, including metal and unpainted wood surfaces
- General purpose bundling, holding, wrapping and waterproofing
- Patching, sealing or seaming applications, including bottom boards

PRODUCT FEATURES

- Professional grade, co-extruded duct tape
- Excellent adhesion to plastic, metal and wood surfaces
- Ideal for patching, sealing or seaming applications and building containments in remediation, restoration and abatement jobs
- All-weather performance to withstand heat and humidity (90 F/80 H) and cold temperatures (25 F)
- Offers 30-day indoor clean removal

CONSTRUCTION

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Blended rubber adhesive

STANDARD WIDTHS

1.88 in; 2.83 in

48 mm; 72 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

Tested in accordance with UL 723

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



Teal
(TBL)



Silver
(SIL)



Black
(BLK)

PHYSICAL PROPERTIES

Adhesion to Stainless Steel

STANDARD

64 oz/in width

METRIC

7.00 N/10 mm

Elongation

23%

23%

Service Temperature Range

25 F to 200 F

-4 C to 93 C

Tensile

26 lbs/in width

45.5 N/10 mm

Thickness - Nominal

10.0 mils

0.25 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

