

PC 618 Duck Pro® by Shurtape®



PC 618 DUCK PRO® BY SHURTAPE® PROFESSIONAL GRADE, INDUSTRIAL COLORED CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- For holding, securing, seaming, repairing, bundling, splicing, packaging, color coding, and masking in HVAC, industrial, commercial, utilities, trucking and automotive applications
- Can also be used as a condensation barrier in appliance assemblies

PRODUCT FEATURES

- Professional grade, industrial duct tape
- Excellent tack, conformability and holding power
- Easy to unwind and tear
- Waterproof backing
- Available in a variety of colors

CONSTRUCTION

Backing: Polyethylene film with a cloth carrier

Adhesive: Natural rubber adhesive

STANDARD WIDTHS

1.88 in; 2.83 in

48 mm; 72 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

Tested in accordance with UL 723

FSI 15/SDI 25

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS

 Olive (OLV)	 Burgundy (BRG)	 Green (GRN)	 Beige (BEI)
 Blue (BLU)	 Brown (BRN)	 Yellow (YEL)	 Orange (ORG)
 Silver (SIL)	 Red (RED)	 Black (BLK)	 White (WHI)

PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	69 oz/in width	7.55 N/10 mm
Elongation	22%	22%
Service Temperature Range	40 F to 200 F	4 C to 93 C
Tensile	26 lbs/in width	45.5 N/10 mm
Thickness - Nominal	9.5 mils	0.24 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

