

PC 657® Duck Pro® by Shurtape®



PC 657® DUCK PRO® BY SHURTAPE® PROFESSIONAL GRADE, HEAVY DUTY, CO-EXTRUDED CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- For use in high performance motorsports applications, pre-manufactured housing and RV assembly, critical industrial applications and for protection during sandblasting and metal-peening operations

PRODUCT FEATURES

- Professional grade, heavy duty, co-extruded duct tape
- Excellent holding power
- Easy to unwind and tear
- Withstands extreme temperature fluctuations
- Waterproof backing

CONSTRUCTION

Backing: Polyethylene film with a cloth carrier

Adhesive: Natural rubber adhesive

STANDARD WIDTH

1.88 in

48 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

Tested in accordance with UL 723

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



Silver
(SIL)



Red
(RED)



Black
(BLK)



White
(WHI)

PHYSICAL PROPERTIES

Adhesion to Stainless Steel

STANDARD

115 oz/in width

METRIC

12.59 N/10 mm

Elongation

20%

20%

Service Temperature Range

40 F to 200 F

4 C to 93 C

Tensile

45 lbs/in width

78.8 N/10 mm

Thickness - Nominal

13 mils

0.33 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

