

SS 501 SHATTERSTOP® SAFETY MIRROR BACKING TAPE

TYPICAL APPLICATIONS

- For use on mirror backs to prevent injury from glass particles and shards in the event of breakage

PRODUCT FEATURES

- SHATTERSTOP® safety mirror backing tape
- Excellent adhesion to mirror backing paints
- Increased thread count for enhanced strength
- Superior mirror protection and dimensional stability

CONSTRUCTION

Backing: Woven polyolefin blend fabric

Adhesive: Acrylic-based adhesive

Liner: Linerless

STANDARD WIDTH

Contact your Shurtape sales representative for available widths

Contact your Shurtape sales representative for available widths

STANDARD LENGTH

333.5 yd

305 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in


APPLICABLE STANDARDS

ANSI Z97.1-2004 Class A & BS EN 12600

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation MD

Tensile

Tensile CD - Weft

Thickness

STANDARD

31 oz/in width

30%

66 lbs/in width

115.58 N/10 mm

6.0 mils

METRIC

3.39 N/10 mm

30%

115.6 N/10 mm

115.58 N/10 mm

0.15 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

