SF 682

SF 682 SHURFLEX® NON-PRINTED METALIZED CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- For use in the HVAC industry for airtight and moisture-free seaming, connecting, splicing, patching and sealing of sheet metal and flex duct, rigid ductboards, air vents, insulation, fibrous filter banks and pollution collection systems

PRODUCT FEATURES

- ShurFLEX® HVAC non-printed professional grade metalized duct tape
- Designed to match sheet metal, flex duct and ductboard
- Flexible and conformable
- Easy to unwind and tear
- Will not twist or curl during application
- Contains low volatile organic compounds (VOCs) to minimize immediate air contamination during use

CONSTRUCTION

Backing: Metalized polyethylene film with a cloth carrier

Adhesive: Natural rubber adhesive

STANDARD WIDTHS

1.88 in; 2.83 in

48 mm; 72 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

Tested in accordance with UL 723

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR

Metalized Silver (MSL)

PHYSICAL PROPERTIES	STANDARD	METRIC
Adhesion to Stainless Steel	55 oz/in width	6.02 N/10 mm
Elongation	23%	23%
Service Temperature Range	50 F to 200 F	10 C to 93 C
Tensile	26 lbs/in width	45.5 N/10 mm
Thickness - Nominal	10.0 mils	0.25 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



Shurtape Technologies, LLC | PO BOX 1530 Hickory, NC 28603-1530 USA | Phone 1.888.442.TAPE (8273) | Fax 800.335.7651 | shurtapetech.com
ISO 9001 CERTIFIED QUALITY SYSTEM
All trademarks listed are the property of Shurtape Technologies, LLC, unless otherwise noted. Form# -SF-682-20261106