# PC 667

## PC 667 SPECIALTY GRADE, OUTDOOR STUCCO DUCT TAPE

### TYPICAL APPLICATIONS

- For protective masking of non-painted surfaces, including steel, vinyl, aluminum and anodized metals
- Use in plastering, stucco, concrete, pool and tile applications
- For protecting window and door frames during stucco applications

### PRODUCT FEATURES

- Specialty grade, outdoor cloth duct tape
- 14-day UV-resistant
- Easy to tear
- Removes cleanly
- Waterproof backing
- Contains low volatile organic compounds (VOCs) to minimize immediate air contamination during use

### CONSTRUCTION

Backing: Waterproof, UV-resistant polyethylene film with a cloth carrier

Adhesive: Blended rubber adhesive

### STANDARD WIDTH

1.88 in

48 mm

### STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

### STANDARD CORE SIZE

3 in

### APPLICABLE STANDARDS

NA

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLORS

Red (RED)

White (WHI)

| PHYSICAL PROPERTIES | STANDARD | METRIC |
|---|---|---|
| Adhesion to Stainless Steel | 40 oz/in width | 4.38 N/10 mm |
| Elongation | 22% | 22% |
| Service Temperature Range | 50 F to 200 F | 10 C to 93 C |
| Tensile | 26 lbs/in width | 45.5 N/10 mm |
| Thickness - Nominal | 9.0 mil | 0.23 mm |

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.




Shurtape Technologies, LLC | PO BOX 1530 Hickory, NC 28603-1530 USA | Phone 1.888.442.TAPE (8273) | Fax 800.335.7651 | shurtapetech.com
ISO 9001 CERTIFIED QUALITY SYSTEM
All trademarks listed are the property of Shurtape Technologies, LLC, unless otherwise noted. Form# -PC-667-20261106